



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

17548 U.S. PTO  
10/758537



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 9 December 2003

**THIS PAGE BLANK (USPTO)**



05MAR03 E789731-3 000073  
P01/7700 0-00-0304948.3

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

JC/SMC/5.3

2. Patent application number

(The Patent Office will fill in this part)

0304948.3

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Brightwell Dispensers Ltd  
Brightwell Industrial Estate  
Ferryfield  
Norton Road  
NEWHAVEN  
East Sussex  
BN9 0JF  
GB

Patents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

348680001

4. Title of the invention

SOAP DISPENSING DEVICE

5. Name of your agent (*if you have one*)

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

G F Redfern & Company  
Lynn House  
Ivy Arch Road  
Worthing  
West Sussex  
BN14 8BX

Patents ADP number (*if you know it*)

1412002

8435356001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)

Date of filing  
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

YES

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -

Description 7

Claim(s) 3

Abstract 1

Drawing(s) 2 + 2 *RM*

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) -

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*) 1

Any other documents -  
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

*S M Camp*

4 March 2003

12. Name and daytime telephone number of person to contact in the United Kingdom



Mrs S M Camp  
01903 820466

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*



# Statement of inventorship and of right to grant of a patent


The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference	JC/SMC/5.3
2. Patent application number (if you know it)	
3. Full name of the or of each applicant	0304948.3
4. Title of the invention	Brightwell Dispensers Limited 2411103 8127394-1 002624 P07/7700 0.00-0304948.3
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	By virtue of Section 39(1)
6. How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))	NONE
7.	I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.  Signature: <i>G. F. Redfern &amp; Co</i> Date: 18 March 2003
8. Name and daytime telephone number of person to contact in the United Kingdom	Mrs S M Camp 01903 820466

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.



Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Etienne Vincent <u>BUNOZ</u> 46 Northbourne Road Eastbourne East Sussex <sup>BN</sup> BN22 8QS
Patents ADP number (if you know it): 08593824001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?



Preferably the base may be provided with a back plate provided with valve carrying means, and container carrying means adapted to position a container adjacent the valve for co-operation with it.

The valve can be of any known type which is adapted to dispense material when it is compressed, and be primed with a quantity of material to be dispensed when it is released. There are many known types of valve which operate in this way, and they will not be described further here.

In a preferred construction the movement of the cover defined by the first hinge means towards the base acts to compress the valve, and the movement away from the base acts to release the valve. Preferably the valve is provided with resilient means which acts against the compression.

In one embodiment the first hinge means can be provided at the top of the base, and the second hinge means can be opposite at the bottom.

Preferably the base and the cover may be provided with side walls, and the cover side walls being disposed outside the base side walls.

The first hinge means can comprise an assembly comprising two lateral sockets provided with resiliently mounted and trigger operated retention means, which are adapted to co-operate with two laterally extending first spigots provided on the inner surface of the walls of the cover. The retention means may comprise a retention member mounted on resilient means and provided with extensions adapted to retain the first spigots in the lateral sockets. The extensions can be provided with angled front surfaces, such that application of the first spigots against them lowers the retention



member against the resilient means, and allows the first spigots to pass into the sockets. With this arrangement the cover can be pressed into place on the base.

To release the first spigots from the sockets and detach the cover from the first hinge means a manually operable and removable trigger portion can be provided which can be readily accessed.

In a preferred construction a second trigger can be provided in the form of troughs provided on the retention member, which can be accessed through slots provided in a top wall of the cover with a tool if the removable trigger portion described above is absent. The troughs can be dimensioned to allow their operation throughout the movement of the cover defined by second hinge means in which the first spigots move from the sockets to the front side of the extensions.

Preferably the second hinge means comprises sockets in the side walls of the base, which are adapted to co-operate with laterally extending second spigots provided on the inner surface of the side walls of the cover. The sockets can be provided with an extended upper edge, against which the second spigots can ride back and forth so as to define the limitation of the movement provided by the first hinge means.

In one construction the second hinge means is also releasable, so the cover can be completely removed from the base. This is facilitated by the cover and the base being constructed from a substantially rigid plastics material, which is provided with sufficient flexibility to allow the cover to be expanded and the base compressed to allow second spigots to be removed from the second hinge means sockets.

The invention can be performed in various ways, but one embodiment will now be described by way of example, and with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a dispensing device according to the present invention in a first arrangement; and,

Figure 2 is a perspective view of the dispensing device as shown in Figure 1 in a second arrangement.

In Figure 1 dispenser 1 comprises base 2, cover 3 and valve (not shown). The cover 3 is releasably attachable to the base 2 by means of first hinge assembly 4 and first spigots 5, the movement of the cover 3 defined by first hinge means acting to operate the valve, as described below.

The cover 3 is also attached to the base 2 by second hinge means, in the form of sockets 6 and second spigots 7, the movement of the cover 3 defined by the second hinge means exposing the base 2 for loading or unloading a container of material to be dispensed (not shown), said movement being prevented unless the cover 3 is detached from the first hinge assembly 4, as described below.

The base 2 comprises a wall mountable back plate 8, side walls 9, valve mounting 10, container mounting 11 and first hinge assembly 4.

The first hinge assembly 4 comprises lateral sockets 13, resiliently mounted retention member 14 and support member 15. The retention member 14 is provided with extensions 16, first removable operating trigger 17 and second operating trigger means in the form of troughs 18. The extensions 16 are provided with an angled front surface 19.

The cover 3 comprises a single component which substantially surrounds the base when fully attached, as shown in Figure 2. It further comprises second operating trigger means slots 20.

In use the dispenser is first opened as shown in Figure 1. The cover 3 is attached to the base 2 by means of sockets 6 and second spigots 7. A valve (not shown) is mounted on mounting 10, and a container (not shown) of material to be dispensed is mounted on mounting 11.

The cover 3 is then rotated about the second hinge means, and the spigots 5 are brought into contact with the first hinge assembly 4, in the direction of arrow A. The first spigots 5 ride the angled front surfaces 19 of the extensions 16, forcing the retention member 14 down. Once the spigots 5 pass the extensions 16, the member 14 rises, and holds the spigots 5 in place in the sockets 13.

The valve (not shown) is provided with a resilient priming and dispensing mechanism, in which the valve is adapted to dispense material when it is compressed, and be primed with material to be dispensed when it is released. When the cover 3 is pressed in the direction of arrow B as shown in Figure 2, the valve is compressed, and material is dispensed downwards from the dispenser 1. When the cover 3 is released, the valve expands under pressure from its resilient means, which pushes the cover 3 back out, and primes the valve with the next portion of material to be dispensed.

The rotational movement of the cover 3 about the first hinge means as described above is limited, thereby to compress the valve a pre-determined amount to dispense a desired quantity of material. The movement of the cover 3 is limited by the shape of sockets 6. When the

cover 3 is attached to the first hinge assembly 4, the second spigots 7 are disposed adjacent the upper edge 6a of the sockets 6 (visible in Figure 1). The spigots 7 are therefore able to ride back and forth along the length of the upper edge 6a.

The cover 3 is further provided with a viewing aperture 21, through which the container can be viewed, and the remaining contents therein determined.

To remove the container for replacement, the trigger 17 is depressed, which lowers the retention member 14 and its extensions 16, which allows the spigots 5 to be removed from the sockets 13, and the cover 3 can be rotated about the second hinge means until it reaches the arrangement as shown in Figure 1. The container and/or the valve can then be removed and/or replaced.

The trigger 17 is formed from a cap, which can be removed from the retention member 14. If the cover 3 is to be removed from the hinge assembly 4 when the trigger 17 has been removed, the troughs 18 can be accessed with a suitable tool through the slots 20. The retention member 14 must be lowered for the duration of the spigot's 5 movement from the back of the sockets 13 to the front side of the extensions 16. Therefore, troughs 18 are long enough to allow the retention member 14 to be accessed through the slots 20 throughout this rotational movement.

The cover 3 and the base 2 are constructed from a rigid plastics material. However, the material is provided with sufficient resilience to allow the second spigots 7 to be removed from the sockets 6 when the cover 3 is expanded and the base 2 is compressed. This allows the dispenser to be completely dismantled for servicing or cleaning.

Thus, a dispenser is provided which can dispense a pre-determined quantity of material in a clean, safe and efficient manner, but which is constructed from the minimum number of parts. Further, a dispenser in which movement of the cover operates the valve is provided with a novel loading mechanism, which allows ready access to the internal compartment.

## Claims

1. A dispensing device comprising a base, a cover and a valve, in which the cover is releasably attached to the base by means of first hinge means, the movement of the cover defined by first hinge means acting to operate the valve, and in which the cover is also attached to the base by second hinge means, the movement of the cover defined by said second hinge means exposing the base for loading or unloading a container of material to be dispensed, said movement defined by the second hinge means being prevented unless the cover is detached from the first hinge means.
2. A dispensing device according to Claim 1 in which the base is provided with a back plate provided with valve carrying means, and container carrying means adapted to position a container adjacent the valve for co-operation therewith.
3. A dispensing device according to Claim 2 in which the valve is adapted to dispense material when it is compressed, and be primed with material to be dispensed when it is released, and in which the movement of the cover defined by first hinge means in a first direction acts to compress the valve, and in a second opposite direction acts to release the valve.
4. A dispensing device according to Claim 3 in which the first hinge means are disposed at a first end of the base, and the second hinge means are disposed at an opposite second end of the base.
5. A dispensing device according to Claim 4 in which the base is provided with side walls, and the cover is also provided with side walls, which are disposed outside the side walls provided on the base in use.

6. A dispensing device according to Claim 5 in which the first hinge means comprises an assembly comprising two lateral sockets provided with resiliently mounted and trigger operated retention means, which are adapted to co-operate with two laterally extending first spigots provided on the inner surface of the walls of the cover.

7. A dispensing device according to Claim 6 in which the retention means comprises a retention member mounted on resilient means and provided with extensions adapted to retain the first spigots in the lateral sockets.

8. A dispensing device according to Claim 7 in which the extensions are provided with angled front surfaces, such that application of the first spigots against the surfaces lowers the retention member against the resilient means, and allows the first spigots to pass into the sockets.

9. A dispensing device according to Claim 8 in which the retention member is provided with a manually operable and removable trigger portion.


10. A dispensing device according to Claim 9 in which the retention member is provided with second trigger means in the form of troughs, which are operable by means of a tool passed through slots provided in a top wall of the cover, and in which the troughs are dimensioned to allow their operation throughout the movement of the cover defined by second hinge means in which the first spigots move from the sockets to the front side of the extensions.

11. A dispensing device according to any of Claims 6 to 10 in which the second hinge means comprises sockets in the side walls of the base, which are adapted to co-operate with laterally extending second spigots provided on the inner surface of the side walls of the cover.
12. A dispensing device according to Claim 11 in which the second hinge means sockets are provided with an extended upper edge, against which the second spigots can ride back and forth so as to define the limitation of the movement provided by the first hinge means.
13. A dispensing device according to any of the preceding Claims in which the second hinge means is releasable, such that the cover can be completely removed from the base.
14. A dispensing device according to Claim 13 in which the cover is provided with a viewing aperture.
15. A dispensing device according to any of the preceding Claims in which the components are constructed from a substantially rigid plastics material.
16. A dispensing device according to Claim 15 in which the substantially rigid plastics material is provided with sufficient flexibility to allow the cover to be expanded and the base compressed to allow second spigots to be removed from the second hinge means sockets.
17. A dispensing device substantially as described herein and as shown in the accompanying drawings.




Abstract


A dispensing device comprising a base, a cover and a valve, in which the cover is releasably attached to the base by means of first hinge means, the movement of the cover defined by first hinge means operating the valve, and in which the cover is attached to the base by means of second hinge means, the movement of the cover defined by second hinge means exposing the base for loading or unloading a container of material to be dispensed, said movement defined by second hinge means only being possible when the cover is detached from the first hinge means.



**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**